



A	Redrawn in 3d	BJA	08-26-09												
REV	Revision Description	By	Date												
DEBUR AND BREAK SHARP EDGES															
Material: Assembly		Weight: 677 LBS													
Treatment: N/A		 The information contained in this drawing is the sole property of Bee Access Products. Any reproduction in part or whole without the written permission of Bee Access Products is strictly prohibited.													
Raw material part number:	Dimensions in [] are in mm Tol. ISO 2768-m														
Assembly	<table border="1"> <tr> <td>></td> <td>0,5</td> <td>6</td> <td>30</td> <td>120</td> <td>400</td> </tr> <tr> <td><</td> <td>6</td> <td>30</td> <td>120</td> <td>400</td> <td></td> </tr> </table>	>	0,5	6	30	120	400	<	6	30	120	400		Tieback Anchor, 6x9 Application (Temporary)	
>	0,5	6	30	120	400										
<	6	30	120	400											
 Scale: 1:3 Size: B/A3	<table border="1"> <tr> <td>TOL.</td> <td>±0.1</td> <td>±0.2</td> <td>±0.3</td> <td>±0.5</td> <td>±0.8</td> </tr> </table>	TOL.	±0.1	±0.2	±0.3	±0.5	±0.8	Machined surfaces 12.5 ISO 1302							
TOL.	±0.1	±0.2	±0.3	±0.5	±0.8										
CAD generated drawing. Do not manually update. Do not scale drawing.		Unless otherwise stated tolerances in inches													
Approvals	By: Date:	Fractions	Decimals												
Drawn	BJA 08-26-09		X ± .060 XX ± .015 XXX ± .005												
Approved	XX-XX-XX		Angles ALL ± .5°												
		Product Line/Project: Rigging													
		REV. A													
		Part No. 950200													
		Sheet 1 of 1													